

KOBRA 300.1 HS

Throat width: 310mm
Security level DIN 66399: P-6 F-3
Security level DIN 32757: 5

Shred size: 0,8x9,5mm cross cut
Paper capacity*: 8-10 A4 70gr; 7-8 A4 80gr

Shreddable Materials: Paper and Films Speed: 0,07m/sec Noise level: 61dba Voltage: 230Volt Power**: 600Watt Waste bag volume: 110 litres Dimensions (WxDxH): 53x43x92cm Weight: 41kg

EAN Code: 8 026064 999267











MAIN FEATURES

High security shredder suitable to shred classified and "Top Secret" documents, equipped with "ENERGY SMART" system with optical illuminated indicators for power saving stand-by mode and environmental protection. A special cutting system can shred an A4 sheet in about 10.000 microchips which become absolutely unreadable even if special electronic optical microscopes are used. Sturdy and reliable mechanical design is guaranteed by the chain drive system SUPER POTENTIAL POWER UNIT with metal gears and special carbon hardened steel cutting knives, which are unaffected by staples and metal clips. The power unit is equipped with continuous duty motor without overheating or duty cycles.

SUPER POTENTIAL POWER UNIT heavy duty chain drive system with metal gears CONTINUOUS DUTY 24 hours countinuous duty operation without overheating and duty cycles CUTTING KNIVES carbon hardened steel cutting knives unaffected by staples and clips ENERGY SMART® power saving stand-by mode just after 8 seconds of non-operation START & STOP automatic start and stop through electronic eyes with stand-by function SAFETY STOP automatic stop with light signal for bag full and / or open door AUTOMATIC REVERSE system in case of jamming CABINET attractive 110 litre cabinet mounted on casters



LED INDICATORS
Easy to operate ON OFF
Reverse switch, with LED
signal for bag full
or open door



CHAIN heavy duty chain drive system and metal gears



ENERGY SMART®
management system
with illuminated indicators
for power saving
in stand-by mode





^{*} Capacity varies on supply power, weight, quality and grain of paper, operating temperature and blade lubrication